# Stainless Steel SS304 SS316 Cam Lock Pipe Fittings Aluminum

## **Basic Information**

Place of Origin: CHINABrand Name: DEYE

Certification: ISO9001:2015 PED

Model Number: DY-QC-15Minimum Order Quantity: 10PCS

• Price: USD2-USD25 each

• Packaging Details: carton box+ ply wooden cases or carton+

**Pallets** 

• Delivery Time: 20 days for usual order, 7 days for stocked

items

Payment Terms: T/T, L/C, D/PSupply Ability: 1000pcs one month



## **Product Specification**

• Highlight: SS316 cam lock pipe fittings,

SS304 cam lock pipe fittings, Aluminum 6 camlock fittings

#### **Product Description**

#### Aluminium Stainless Steel SS304 SS316 Camlock Couplings Quick Couplings Factory

Camlock couplings are well-known as quick hose coupling providing quick connection and disconnection for pumps, tanks, equipment, Stainless steel cam lock fittings allow for quick and secure hose connections. The camlock couplings mate by inserting the grooved coupling into the cam coupling and simply closing the cam or lever arms. Safety pins or locks prevent the cam arms from accidental disconnection during use.

#### Product Information/Product Description/Basis Information/Specification

Comlock Types:	Type A, Type B, Type C, Type D, Type E, Type F, Type DC, Type DP, Type DW
Sizes	1/2", 3/4",1",1 1/4", 1 1/2", 2", 2 1/2", 3", 4", 5", 6" 8"10" 12"
Working Pressure	5 kg/cm2 to 20 kg/cm2 (working varies according to the size of coupling )
Material	Aluminium,Bronze, Carbon Steel,S.S.304, S.S.316 PP / Cement,Fertilizers,Fire Fighting Equipment,Ink / Dye /
	Paint Industries ,Petrochemical / Refineries / Process Industries, Mining, Oil Drilling Companies
Application	(offshore / onshore ), Railways, Steel Plants, Military, Applications, Pneumatic Conveyors, Oil Blending Plants,
	Automobile manufacturers, Chemical Industries and Furnaces.

#### Features /Advantages:

- 1. Simple structure, convenient operation, quick connect and open it
- 2. compact size, light weight, good sealing and interchangeability
- 3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium
- 4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc
- 5. Cam & groove couplings are easy to operate. Camlock consists of two parts male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power
- 6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications

#### Types of the cam & groove couplings



316 SS Camlock quick coupling Male camlock adaptor inner thread



316 SS Camlock coupler Female camlock coupler outer thread

## Type A

camlock A50 camlock A75 camlock A100 camlock A125
camlock A100
camlock A125
Odinio On Prizo
camlock A150
camlock A200
camlock A250
camlock A300
camlock A400
camlock A500
camlock A600

Size:	Product no:
1/2"	camlock B50
3/4"	camlock B75
1"	camlock B100
1 1/4"	camlock B125
1 1/2"	camlock B150
2"	camlock B200
2 1/2"	camlock B250
3"	camlock B300
4"	camlock B400
5"	camlock B500
6"	camlock B600





316 SS Camlock hose tail coupling Female camlock coupler with serrated hose tail

## Type C


Size:	Product no:	
1/2"	camlock C50	
3/4"	camlock C75	
1"	camlock C100	
1 1/4"	camlock C125	
1 1/2"	camlock C150	
2"	camlock C200	
2 1/2"	camlock C250	
3"	camlock C300	
4"	camlock C400	
5"	camlock C500	
6"	camlock C600	

#### 316 SS Camlock lever coupling Female snaplock coupler inner thread

## Type D

	Size:	Product no:
	1/2"	camlock D50
	3/4"	camlock D75
	1"	camlock D100
	1 1/4"	camlock D125
	1 1/2"	camlock D150
	2"	camlock D200
2 1/2" 3" 4" 5"	2 1/2"	camlock D250
	3"	camlock D300
	4"	camlock D400
	5"	camlock D500
	6"	camlock D600





## Type E

Size:	Product no:	
1/2"	camlock E50	
3/4"	camlock E75	
1"	camlock E100	
1 1/4"	camlock E125	
1 1/2"	camlock E150	
2"	camlock E200	
2 1/2"	camlock E250	
3"	camlock E300	
4"	camlock E400	
5"	camlock E500	
6"	camlock E600	



316 SS Camlock quick coupling Male camlock adaptor outer thread

## Type F

Size:	Product no:	
1/2"	camlock F50	
3/4"	camlock F75	
1"	camlock F100	
1 1/4"	camlock F125	
1 1/2"	camlock F150	
2"	camlock F200	
2 1/2"	camlock F250	
3"	camlock F300	
4"	camlock F400	
5"	camlock F500	
6"	camlock F600	





### 316 INOX Camlock Dustplug

## Type DP

Size:	Product no:	
1/2"	camlock DP50	
3/4"	camlock DP75	
1"	camlock DP100	
1 1/4"	camlock DP125	
1 1/2"	camlock DP150	
2"	camlock DP200	
2 1/2"	camlock DP250	
3"	camlock DP300	
4"	camlock DP400	
5"	camlock DP500	

camlock DP600

#### 316 INOX Camlock Dust cap

#### Type DC

Size:	Product no:
1/2"	camlock DC50
3/4"	camlock DC75
1"	camlock DC100
1 1/4"	camlock DC125
1 1/2"	camlock DC150
2"	camlock DC200
2 1/2"	camlock DC250
3"	camlock DC300
4"	camlock DC400
5"	camlock DC500
6"	camlock DC600

## Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

#### Our Service

- 1. Technical support
- 2. Raw Material Quality control.
- 3. Inspection during the production time.
- 4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
- 5. Test Report each shipment
- 4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
- 5. Flexible payment Ways: LC. TT. DP
- 6. Customized Package includes Logo. Cases Dimension.
- 7. 18 months quality Guarantee time.
- 9. Free replacement by air if any error founded
- 10. 24 hours to Feedback your questions

## SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



+8613292824811



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China